



Zertifiziertes
QM-System
DIN EN ISO 9001
Zertifikat-Nr. 01017

Rotating Vane Flow Indicator

Threaded Connections



measuring
•
monitoring
•
analysing



- Indication range:
0.03-0.1 ... 5-150 L/min water
- p_{max} 16 bar, t_{max} 110°C
- Connection:
G 1/8... G 1 1/2
NPT on request
- Material: Trogamide,
PSU, nickel plated brass,
stainless steel



KOBOLD companies worldwide:

ARGENTINA, AUSTRIA, BELGIUM, CANADA, CHILE, CHINA, CZECHIA,
FRANCE, GERMANY, GREAT BRITAIN, INDIA, INDONESIA, ITALY,
MALAYSIA, MEXICO, NETHERLANDS, POLAND, SINGAPORE, SLOVAKIA,
SPAIN, SWITZERLAND, THAILAND, USA, VENEZUELA, VIETNAM

KOBOLD Messring GmbH
Nordring 22-24
D-65719 Hofheim/Ts.
☎ +49(0)6192 299-0
Fax +49(0)6192 23398
E-Mail: info.de@kobold.com
Internet: www.kobold.com

Model:
DAF-1



Application and Operating Principle


The KOBOLD Rotating Vane Flow Indicator is applied where visual flow indication without flow measurement is required. A square housing with transparent windows front and back, contains a rotating vane whose rotary motion, caused by the flowing medium, indicates presence of “flow”.

Within the same housing dimensions, differing minimum and maximum flow ranges are obtained by changing the inlet port orifice. The instruments can be installed in any position.

Flow, however, must be in the direction indicated by the arrow.

They are pivot-mounted, which enables the sight glass of the indicating unit to be turned to an optimum viewing direction even during operation (not with material combination DAF-14...).

Dimensions



Material Combination

DAF:	11...	12...	13...	14...
Housing:	Trogamide	PSU	nickel plated	st. st.
Housing cover:	Trogamide	PSU	PSU	PSU
Threaded connections:	nickel plated brass	st. steel ¹	nickel plated brass	st. st. ¹
Locking pins:	brass	brass	brass	–
O rings:	NBR	FPM	NBR	FPM
Rotating vane:	POM	PTFE	POM	PTFE
Axle:	st. st. ¹	st. st. ¹	st. st. ¹	st. st. ¹
Axle bearing:	PTFE	PTFE	PTFE	PTFE
Max. operating pressure:	10 bar	10 bar	16 bar	16 bar
Max. operating temperature:	60°C	110°C	110°C	110°C

¹⁾ Material code 1.4571

Installation hints

- The instruments can be installed in any position. Flow however must be in the direction of arrow.
- PTFE tape to be used for sealing of connections.
- During installation, housing fittings must be held static to avoid transmission of stresses into the housing.
- During operation, observe that the maximum permitted flow is not exceeded, otherwise under certain conditions, this can lead to damage to the rotating vanes.

Connections

G 1/8 R06	G 1/4 R08	G 1/2 R015	G 3/4 R020	G 1 R25	G 1 1/4 R32	G 1 1/2 R40
1/8 NPT N06	1/4 NPT N08	1/2 NPT N15	3/4 NPT N20	1 NPT N25	1 1/4 NPT N32	1 1/2 NPT N40

Order Details (Example: DAF-1101H R08)

Indication range		Model				Connection			
[L/min] water	Δ P [bar]	DAF-11..	DAF-12..	DAF-13..	DAF-14..	G-thread		NPT-thread	
0.03...0.1	0.25	DAF-1101H..	DAF-1201H..	DAF-1301H..	DAF-1401H..	R06	R08	N06	N08
0.03...0.5	0.8	DAF-1102H..	DAF-1202H..	DAF-1302H..	DAF-1402H..	R06	R08	N06	N08
0.2...3	0.85	DAF-1103H..	DAF-1203H..	DAF-1303H..	DAF-1403H..	R06	R08	N06	N08
0.5...12	0.55	DAF-1104H..	DAF-1204H..	DAF-1304H..	DAF-1404H..	R08	R15	N08	N15
1...25	0.35	DAF-1105H..	DAF-1205H..	DAF-1305H..	DAF-1405H..	R15	R20	N15	N20
2...50	0.35	DAF-1106H..	DAF-1206H..	DAF-1306H..	DAF-1406H..	R20	R25	N20	N25
5...150	1.25	DAF-1107H..	DAF-1207H..	DAF-1307H..	DAF-1407H..	R32	R40	N32	N40

Rotating Vane Flow Indicator

Flanged Connections



- Indication range:
0.03-0.1 ... 5-150 L/min water
- p_{max} 16 bar, t_{max} 110°C
- Connection:
DN 15...DN 50; 1/2" ... 2" ANSI
- Material:
housing: stainless steel
cover: PSU

KOBOLD companies worldwide:

ARGENTINA, AUSTRIA, BELGIUM, CANADA, CHILE, CHINA, CZECHIA,
FRANCE, GERMANY, GREAT BRITAIN, INDIA, INDONESIA, ITALY,
MALAYSIA, MEXICO, NETHERLANDS, POLAND, SINGAPORE, SLOVAKIA,
SPAIN, SWITZERLAND, THAILAND, USA, VENEZUELA, VIETNAM

KOBOLD Messring GmbH
Nordring 22-24
D-65719 Hofheim/Ts.
☎ +49(0)6192 299-0
Fax +49(0)6192 23398
E-Mail: info.de@kobold.com
Internet: www.kobold.com


Model:
DAF-2



Application and Operating Principle

The KOBOLD Rotating Vane Flow Indicator is applied where visual flow indication without flow measurement is required. A square housing with transparent windows front and back, contains a rotating vane whose rotary motion, caused by the flowing medium, indicates presence of “flow”. Within the same housing dimensions, differing minimum and maximum flow ranges are obtained by changing the inlet port orifice. The instruments can be installed in any position. Flow, however, must be in the direction indicated by the arrow. Connection is made by means of stainless steel flanges in accordance with DIN/Form C in standard sizes DN 15, 25, 40 or 50.

Dimensions



Materials	
Housing:	stainless steel 1.4571 / 1.3955
Housing cover:	PSU
Connection:	stainless steel 1.4571
O rings:	FPM
Rotating vane:	PTFE
Axle:	stainless steel 1.4571
Axle bearing:	PTFE

Technical Details

Max. operating pressure: 16 bar
 Max. operating temperature: 110 °C

Installation

- The instruments can be installed in any position. Flow, however, must be in the direction of arrow.
- Flat gaskets must be used for sealing of flanges.
- During operation, observe that the maximum permitted flow throughput is not exceeded, otherwise under certain conditions, this can lead to damage to the rotating vanes.

DN	D [mm]	K [mm]	d 4 [mm]	d 2 [mm]	Number of screws
15	95	65	45	14	4
25	115	85	68	14	4
40	150	110	88	18	4
50	165	125	102	18	4

Order Details (Example: DAF-2401H F15)

Indication range		Model	Connection DIN-Flange				Connection ANSI-Flange			
[L/min] Water	Δ P [bar]		DN15 PN16	DN25 PN16	DN40 PN16	DN50 PN16	1/2" 150 lbs	1" 150 lbs	1 1/2" 150 lbs	2" 150 lbs
0.03...0.1	0.25	DAF-2401H..	F15				A15			
0.03...0.5	0.8	DAF-2402H..	F15				A15			
0.2...3	0.85	DAF-2403H..	F15				A15			
0.5...12	0.55	DAF-2404H..	F15	F25			A15	A25		
1...25	0.35	DAF-2405H..	F15	F25	F40		A15	A25	A40	
2...50	0.35	DAF-2406H..		F25	F40			A25	A40	
5...150	1.25	DAF-2407H..		F25	F40	F50		A25	A40	A50